



#6  
DAC  
PATENT  
2119-0171P

IN THE U. S. PATENT AND TRADEMARK OFFICE

APPLICANTS: John R. KARPINSKY et al. CONF.: 4198  
APPLN. NO.: 10/025,460 GROUP:  
FILED: December 26, 2000 EXAMINER:  
FOR: FIBER OPTIC SWITCH PROCESS AND OPTICAL  
DESIGN

REQUEST FOR RECONSIDERATION

Commissioner for Patents  
**Box DAC**  
Washington, D.C. 20231

December 23, 2002

Sir:

Responsive to the Decision Refusing Status Under 37 C.F.R. § 1.47(a) mailed August 23, 2002, the period for response having been extended two (2) months to expire on December 23, 2002, the following Remarks are respectfully submitted in connection with the above-identified application.

DOCUMENTS

Attached hereto, please find the executed Declaration of the missing inventor, John R. Karpinsky, attached to a copy of the application as filed, thereby completing the filing requirements of the above-identified application.

REMARKS

Although numerous attempts were made to contact the John R. Karpinsky through various internet methods, we were unsuccessful. However, upon trying the

12/26/2002 CNGUYEN 00000104 10025460

01 FC:2252

200.00 OP

**RECEIVED**

DEC 27 2002

OFFICE OF PETITIONS

service supplied by the Petitions Attorney in this matter, we were finally able to locate the inventor, who has since executed both the Declaration and Assignment documents for this application. The undersigned thanks the Petitions Attorney for her assistance in this matter.

Pursuant to 37 C.F.R. §§ 1.17 and 1.136(a), Applicants respectfully petition for a two (2) month extension of time for filing a reply in connection with the present application, and the required fee of \$200.00 is attached hereto.

If necessary, the Commissioner of hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. § 1.16 or under § 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By: 

Michael K. Mutter  
Reg. No. 29,680

MKM/gf  
(703) 205-8000  
2119-0171P

P.O. Box 747  
Falls Church, VA 22040-0747



## FIBER OPTIC SWITCH PROCESS AND OPTICAL DESIGN

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

5           The present invention is related to fiber optic switching. In particular, the present application is related a micromachine actuated fiber optic switch and a process for making and using same.

#### 2. Description of Related Art

10           With the rapid growth of the fiber optic based communications and computing, there is now and will continue to be a persistent need for capabilities to switch fiber optic signals. In addition, because of ever decreasing form factors, there is a corresponding need to provide fiber optic switching capabilities in ever smaller package sizes.

15           Conventional systems for switching or directing fiber optic signals tend to be undesirable in that large mirrors and supporting apparatus are required which give rise to undue expense, unreliability, and inconsistency in optics. Moreover, problems with process control particularly for micromachine parts give rise to inconsistent yield and  
20           inconsistency in performance between parts manufactured according to switch design.

Fiber optic switch design and optics design are integrally related because fabrication methods are deeply influenced by the size, shape, and

**RECEIVED**

DEC 27 2002

OFFICE OF PETITIONS

structure of the optics, which factors ultimately determine what methods are feasible. One goal is to minimize assembly costs. However, since fibers used in fiber optic communication are typically manufactured separately from the switch, they must be assembled into a final product.

5 Other parts may also need to be manually placed into a manufactured switch design if necessary and sufficiently simple. Although high volume manufacture may involve robotic assembly, delicate placement and alignment of optical fibers in switch assemblies still poses practical difficulties and costs.

10 Accordingly, it is would be appreciated in the art for a method and apparatus for switching fiber optic signals and a process for making and using same which overcomes these and other difficulties. Such a method and apparatus would provide for placement and alignment of optical components, such as optical fibers and the like within switch assemblies.

15 **SUMMARY OF THE INVENTION**

Therefore in accordance with various exemplary embodiments of the present invention, a method and apparatus for switching optical signals are described. The optical switch of the present invention may include a first optical input/output port, plurality of second optical input/output  
20 ports, and an optical guiding assembly coupled therebetween. The optical guiding assembly is preferably configured to moveably direct an optical signal between the first optical input/output port and a selected one of the plurality of second optical input/output ports.

Alternatively, the optical guiding assembly further preferably includes a optical micro-element assembly, and an actuator assembly, which actuator assembly may be mechanically coupled to the optical micro-element assembly and may be configured to moveably direct the optical micro-element assembly to a predetermined position. It should be noted that the predetermined position corresponds to a placement of the actuator sufficient to cause the optical micro-element assembly to direct the optical signal to the selected one of the optical input/output ports.

As will be described in greater detail hereinafter, the optical micro-element assembly in accordance with various exemplary embodiments may include various structures capable of directing and or deflecting light signals such as for example, a micro-lens, an etched lens, a ball lens, a mirror, and the like and the actuator assembly may include, for example, a comb drive, which comb drive may be integrated into the substrate through the use of, for example, micro-machining, semiconductor-style device manufacturing techniques, or the like.

Thus in accordance with various exemplary embodiments an actuating assembly may be integrated into the substrate and an optical micro-element integrated into the actuating element. The process used for integration may include Deep Reactive Ion Etching (DRIE). It should be noted that the optical micro-element has an optical axis parallel to a horizontal plane associated with the substrate and accordingly the actuating assembly is configured to move the optical micro-element within

the horizontal plane. The switch assembly may preferably include a first input/output port and a plurality of second input/output ports. The optical signal is directed to a selected one of the plurality of second input/output ports from the first input/output port by moving the optical micro-element within the horizontal plane in a direction perpendicular to the optical axis using the actuating assembly. In order to control the movement and precision of the actuating assembly a feedback controller and a plurality of sensors may be used. Accordingly, one of the plurality of sensors corresponding to the selected input/output port generates a feedback signal associated with, for example, a level of alignment of the optical signal. It will be appreciated that signal intensity maxima, for example, may be used as an indication of alignment. The feedback signal may then be used to correct the position of the actuator assembly so as to correct the level of alignment.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will become more fully understood from the detailed description given herein below and the accompanying drawings, which are given by way of illustration only, and thus are not limitative of the present invention, and wherein:

FIG 1A is a diagram illustrating an exemplary ball lens in accordance with the present invention in a deflection position;

FIG 1B is a diagram illustrating an exemplary ball lens in accordance with the present invention in a center position;

FIG 1C is a diagram illustrating an exemplary composite of FIG 1a and FIG 1b in accordance with the present invention;

FIG 2A is a diagram illustrating a top view of an exemplary layout of a lens position and fiber positions in accordance with the present invention;

FIG 2B is a diagram illustrating the exemplary layout shown in FIG 2A and further illustrating an exemplary feedback mechanism in accordance with the present invention;

FIG 3 is a diagram illustrating an exemplary top cross-sectional view of an array input fibers and an output fiber in accordance with the present invention;

FIG 4 is a diagram illustrating a cross-sectional view of an exemplary fiber input in accordance with the present invention;

FIG 5 is a diagram illustrating an exemplary fiber optic multiplexer linear motor and optical micro-element assembly in accordance with the present invention; and

FIG 6 is a diagram illustrating cross-sectional views of exemplary output fibers in accordance with the present invention.

#### **DETAILED DESCRIPTION OF THE INVENTION**

A micro-machine actuator in accordance with exemplary embodiments of the present invention may be fabricated using single crystal silicon. Exemplary fabrication processes use Deep Reactive Ion Etching (DRIE) to configure the silicon and the micro-machine actuators

as is described in greater detail in U.S. Provisional Application No. 60/238,437 entitled "DEEP GRAYSCALE ETCHING OF SILICON" filed October 10, 2000 which document is incorporated herein by reference. Exemplary optics may be made using a suitable grade of optical glass such as, for example, Borosilicate Crown Glass, e.g. BK7 grade A optical glass, BAF10, SKN8, SK11, sapphire, or the like as would be known to one of skill in the art. Thus, for the purpose of discussion, BK7 glass balls may be used as ball lenses in accordance with various exemplary embodiments of the present invention although other grades of glass may be used for ball lenses as discussed hereinabove. BK7 optical glass balls may be manually placed in receptacles in the etched silicon. Fibers may be manually placed in grooves in the silicon that will guide them to the proper position as is discussed in greater detail in U.S. Patent Application Serial No. 09/556,793.

It should be noted that an exemplary baseline design in accordance with various exemplary embodiments of the present invention uses a single mode fiber with a numerical aperture of approximately 0.13, a core diameter of 8 to 12 microns, and a cladding diameter of 125 microns. Exemplary processes in accordance with the present invention can work with other configurations, but the base line configuration as described is both highly manufacturable and highly useful for bi-directional fiber telecommunications.

Various views of an exemplary optical design in accordance with the present invention are illustrated in FIG 1A-1C. In this exemplary design, optical micro-elements may include ball lenses. It should be noted that ball lenses are shown in FIG 1A-1C from the top view. FIG 1A shows  
5 input ball lens 110 associated with input signal 111, and movable ball lens 120 imposing a maximum deflection to the left position of input signal 111 to output ball lens 130 at angle  $\Theta$  131. FIG 1B shows input ball lens 110 associated with input signal 111 and movable ball lens 120 in a center position such that input signal 111 is directed toward output  
10 ball lens 140 at angle  $\Theta'$  141. FIG 1C shows a composite of both positions illustrated in FIG 1A and FIG 1B showing the relative position changes of movable ball lens 120.

It should be noted that while FIGs 1A-1C described above show movable ball lens 120 in a center position and one extreme deflection  
15 position, movable ball lens 120 may be used to deflect the input beam to a maximum deflection position in the other direction, e.g. -  $\Theta$  131 (not shown). Thus, the maximum angle for  $\Theta$  131 is preferably about +/- 48 degrees. Maximum deflection parameters along with factors such as, for example, the size of optical fibers, sets the distances and the number of  
20 fibers that can be handled in a switch in accordance with the present invention. Accordingly, the optical design as is partially illustrated in FIG 1A-1C forms the basis for an exemplary micro-machine actuator design capable of moving, for example, movable ball lens 120 to deflect a light

signal such as input signal 111 from one input fiber to one of several output fibers. While several variations are possible in accordance with various exemplary embodiments of the present invention, switches having a smaller number of output fibers allow for the widest tolerances for component dimensions and placement accuracy.

It should further be noted that while movable ball lens 120 is shown directing input signal 111 to various positions, it is contemplated that various exemplary embodiments in accordance with the present invention may include a variety of optical guiding devices or optical micro-  
10 elements such as lenses, mirrors, facets, diffraction gratings, and the like capable of directing an optical signal to one or more optical input/output ports. For example, as will be described in greater detail herein after, movable ball lens 120 may be replaced with one or more etched lenses. As will be appreciated by those skilled in the art, many alternative devices  
15 may be constructed having lens like properties. However, it should be understood that devices other than lenses, such as, for example, mirrors and the like may also be used to direct light signals in accordance with the present invention.

The exemplary implementation shown schematically in FIG 2A is for  
20 eight-to-one switch 200. Input fiber 212 may be coupled into base 210 having ball lens 211 for focusing input signal 213. While an actuator is not shown, movable ball lens 220 may be moved to deflect input signal 213 to one of the output fibers 232a-232h. Thus deflected signals 221a-

221h may be transmitted to corresponding output ball lenses 231a-231h which are secured in based 230 and may be coupled to corresponding output fibers 232a-232h. Again it should be noted that while several signals 221a-221h are shown simultaneously, input signal 213 is  
5 preferably deflected to only one output position at a time.

The exemplary optical design uses spheres preferably of 300 micron diameter for ball lenses such as ball lens 211, 220, and 231a-231h. Distance 222 from the center movable ball lens 220 to ball lenses 231a-231h placed at the fiber apertures of base 230 is 1.9 mm for the  
10 exemplary eight-to-one switch 200 resulting in an actuator chip size of approximately 4 by 6 mm including space for bonding pads and fiber holders. As will be appreciated by those skilled in the art, the cost of larger switches will be greater than the cost of the smaller switches, but all are well within the limits of manufacturing.

15 It should be noted that while FIG 2A and 2B illustrates signal 213 carried on an exemplary single fiber input being switched to one of several fiber outputs, the present invention allows for several inputs to be switched to a single output. Further, signal 213 may include bi-directional communication signals as are known in the art and which  
20 may, for example, be multiplexed in the time domain or the like such that input and output may both be conducted in accordance with the present invention. In addition, the position of, for example, movable ball lens 220

may be controlled through the use of a feedback mechanism as illustrated in FIG 2B.

Thus in accordance with various exemplary embodiments, the position of, for example, movable ball lens 220 may be controlled through  
5 feedback processor 240, which may be a separate processor, an analog circuit, a software routing in a central processing core or the like as would be appreciated by one skilled in the art. Optical signal 213 may be directed to one of the input/output ball lenses 231a-231h by applying a control voltage to actuator elements 242a and 242b which may be part of,  
10 for example, a comb drive as will be described in greater detail hereinafter. Feedback processor 240 preferably receives a feedback value of some kind such as, for example, a voltage level, from sensors 241a-241h, which sensors may provide an indication of a factor related to the intensity level of optical signal 213. In this way, directional alignment of  
15 movable ball lens 220 may be achieved with a high degree of precision. It will further be appreciated that the control voltage applied to actuating elements may take a variety of forms including, for example, step voltages, continuous analog voltages, or the like, or a hybrid of many forms of control signal. It will further be appreciated that in accordance with a  
20 preferred embodiment, feedback processor 240 may also contain memory 250 for storing predetermined feedback values or the like obtained during, for example, a calibration procedure to expedite the convergence of the directed optical signal 213 to a maximum intensity corresponding to

optimum alignment with the center of the selected input/output lens 231 during operation.

FIG 3 illustrates array 300 of input fibers 321a-321l shown in a top view with the fibers shown in cross section to show respective fiber cores.

5 All twelve input fibers 321a-321l may accept optical input, but only one signal carried on a selected one of input fibers 321a-321l will pass to output fiber 315 when output fiber lens 312a is in the proper position. It should be noted that lenses 312a and 312b and 322a-322l may be cylindrical lenses with no focusing power in the vertical direction. Fibers  
10 321a-321l may, in the present embodiment, be manually placed in the grooves provided on substrate 320, which substrate also holds lenses 322a-322l as described in U.S. Patent Application Serial No 09/556,793. It should be noted however that lenses described in U.S. Patent Application Serial No 09/556,793, are primarily arranged with an optical  
15 axis perpendicular to the plane of the substrate whereas, in accordance with various exemplary embodiments of the present invention, optical micro-elements or lenses may be aligned with the optical axis parallel to the plane of the substrate. Fiber 315 may further be manually placed on substrate 310 which substrate holds lenses 312a and 312b and micro-  
20 machine actuator 314 which is preferably a comb drive actuator to be described in greater detail hereinafter and may be further described in related U.S. Provisional Application Serial No: 60/174,164 as cited herein above. Micro-machine actuator 314 selects the angle of acceptance from

- 12 -

input fibers 321a-321l to output fiber 315. It should be noted that while the exact manufacturing method for various portions of the exemplary fiber optic switch in accordance with the present invention may vary, reactive ion etching may be used to configure etched lenses in a preferred  
5 embodiment. Further, conventional deposition techniques may be used to deposit metal structures comprising, for example, micro-machine actuator 314 or comb drive, as well as guides for the fiber positioning which may be constructed from a suitable metal including, for example, Silicon.

FIG 4 illustrates an exemplary input fiber 440 with its optics. As  
10 will be appreciated, input fiber 440 is similar to exemplary output fibers however does not require a comb drive to move lens 421. Lens 421 is preferably an etched lens as opposed to a ball lens in alternative exemplary embodiments, and may be fabricated at the same time as the movable lens for the output fiber by reactive ion etching.

15 Thus, in accordance with various exemplary embodiments of the present invention, a fiber optic multiplexer linear motor and optical micro-element assembly 500 is illustrated in FIG 5. Optical fiber 510 may be placed in fiber guide 520 and positioned such that the end of optical fiber 510 abuts fixed optical micro-element 530. Movable optical micro-  
20 element 540 may be positioned along direction of travel 541 by the action of motor rotor 550 and motor stator 560 comprising an electrostatic comb drive. As can be seen, motor rotor 550 pieces are fixed to the edges of movable optical micro-element 540 such that motor rotor 550 pieces

- 13 -

cause the linear motion of movable optical micro-element 540 along direction of travel 541. It should be noted that springs 570 may be used to establish return positions of movable optical micro-element 540 preferably to a center position and may be anchored to substrate 590 by  
5 anchors 580. Accordingly, motion may be achieved in either direction by energizing the appropriate motor stator 560 corresponding to the desired direction. Alternatively, springs 570 may be omitted and complimentary voltages applied to the stator on the opposite side of the direction of pull. In addition, feedback mechanisms may be used to determine that the  
10 position of movable optical micro-element 540 has reached a desired position.

Further in accordance with various exemplary embodiments of the present invention, the position of movable optical micro-element 540 may be set using a series of, for example, step voltages which correspond to  
15 the desired position of optical micro-element 540 with respect to one of the plurality of input/output fibers in an array. The preferred position corresponds to a maximum intensity of an optical signal coupled between an input/output fiber and a selected one of the input/output fibers in an array and may be determined empirically, using feedback, using stored  
20 position information, or the like.

In accordance with various alternative exemplary embodiments, FIG 6 illustrates output optics and fiber for an exemplary fiber optic switch in accordance with the present invention. As can be seen, movable optical

- 14 -

micro-element 631a is in the undeflected position, while movable optical micro-element 631b is deflected such that it will accept light signal 650 from a left most input fiber (not shown). It should be noted that voltages 660a-b and 661a-b, applied to comb drive stators 633a-b and 634a-b  
5 controls the position of lenses 631a-b by acting on corresponding comb drive rotors 632a-b and 635a-b.

The invention being thus described, it will be obvious that the invention may be modified in various ways. Such minor variations however are not to be regarded as a significant departure from the  
10 invention and all such modifications are intended where appropriate to fall within the scope of the appended claims.

1 We claim:

2 1. An optical micro-switch comprising:  
3 a generally planar substrate;  
4 a first optical input/output port;  
5 a plurality of second optical input/output ports; and  
6 an optical guiding assembly operatively coupling first optical  
7 input/output port to at least one of said plurality of second optical  
8 input/output ports along one of plural optical paths, each of said optical  
9 paths being generally parallel to said generally planar substrate, the  
10 optical guiding assembly configured to moveably direct an optical signal  
11 between the first optical input/output port and a selected one of the  
12 plurality of second optical input/output ports.

1 2. The optical switch of claim 1, wherein the optical guiding assembly  
2 further includes:  
3 a optical micro-element assembly including an optical  
4 microelement; and  
5 an actuator assembly coupled to the optical micro-element  
6 assembly, the actuator assembly configured to move at least said optical  
7 micro-element substantially parallel to said generally planar substrate to  
8 a predetermined position so that said optical micro-element directs  
9 optical signals along a selected optical path between said first optical

10 input/output port to a selected one of said plurality of second optical  
11 input/output ports.

1 3. The optical switch of claim 2, wherein the actuator assembly  
2 further includes a horizontal electrostatic comb drive.

1 4. The optical switch of claim 2, wherein the optical micro-element  
2 includes a lens mounted to have an intended optical path generally  
3 parallel to said generally planar substrate.

1 5. The optical switch of claim 2, wherein the optical micro-element  
2 includes an optical glass ball lens.

1 6. The optical switch of claim 2 wherein there are at least three  
2 second optical input/output ports, said optical micro-element assembly  
3 switching said optical micro-element to plural positions corresponding in  
4 number to the number of said plurality of second optical input/output  
5 ports.

1 7. An optical micro-switch comprising:  
2 a first optical input/output port;  
3 a plurality of second optical input/output ports; and

4 an optical guiding assembly operatively coupling first optical  
5 input/output port to at least one of said plurality of second optical  
6 input/output ports along one of plural optical paths, said optical guiding  
7 assembly including,

8 a horizontal electrostatic comb drive, and

9 an optical micro-element operably connected to said comb  
10 drive,

11 said comb drive moving said optical micro-element to plural  
12 positions greater than two and corresponding in number to plural  
13 input/output ports, to direct an optical signal between said first  
14 optical port and a selected one of said second optical input/output  
15 ports.

1 8. The optical micro-switch of claim 7 wherein at least one of said  
2 input and output ports has plural channels.

1 9. The optical switch of claim 7, wherein the actuator assembly  
2 further includes a horizontal electrostatic comb drive.

1 10. The optical switch of claim 7, wherein the optical micro-element  
2 includes an lens mounted to have an intended optical path generally  
3 parallel to said generally planar substrate.

1 11. The optical switch of claim 7, wherein the optical micro-element  
2 includes an optical glass ball lens.

1 12. A method for switching an optical signal between a first optical  
2 input/output port and at least one of a plurality of second optical  
3 input/output ports the method comprising:

4 a) providing said first and second optical input/output ports in  
5 an arrangement generally parallel to a generally planar supporting  
6 substrate;

7 b) providing an micro-optical element between said first optical  
8 input/output port and said plurality of second optical input/output  
9 ports, an optical path generally parallel to said supporting substrate  
10 being defined between said first optical input/output port and said  
11 micro-optical element;

12 c) directing the optical signal between the first optical  
13 input/output port and a selected one of the plurality of second  
14 optical input/output ports by shifting said micro-optical element in  
15 a direction transverse to said optical path.

1 13. The method of claim 12 wherein there are at least three second  
2 optical input/output ports, said step c) of directing switching said optical  
3 micro-element to plural positions corresponding in number to the number  
4 of said plural second optical input/output ports.

1 14. The method of claim 12, wherein the actuator assembly further  
2 includes a horizontal electrostatic comb drive.

1 15. The method of claim 12, wherein the optical micro-element  
2 assembly includes an etched lens.

1 16. The method of claim 12, wherein the optical micro-element  
2 assembly includes an optical glass ball lens.

1 17. The method of claim 12, wherein the optical micro-element  
2 assembly includes a mirror.

1 18. An optical switch comprising:  
2 a generally planar substrate;  
3 an actuating assembly integrated into the substrate; and  
4 an optical micro-element integrated into the actuating assembly,  
5 wherein the optical micro-element has an optical axis parallel to the plane  
6 of said substrate, and wherein the actuating assembly is configured to  
7 move the optical micro-element parallel to the plane of said substrate.

1 19. The optical switch of claim 13, further comprising:  
2 an first input/output port; and

- 20 -

3           a plurality of second input/output ports, wherein an optical signal  
4   is directed to a selected one of the plurality of second input/output ports  
5   from the first input/output port by driving an actuator to move the optical  
6   micro-element within the plane of said substrate, said actuator being an  
7   horizontal electrostatic comb drive.

ABSTRACT

A method and apparatus for optical switching is described wherein a first optical input/output port and plurality of second optical input/output ports are coupled using an optical guiding assembly. An optical signal may thereby be movably directed between the first  
5 input/output port and a selected one of the second optical input/output ports. The optical guiding assembly includes a optical micro-element assembly and an actuator assembly which moveably directs the microlens assembly to a predetermined position corresponding to the selected one of the input/output ports. The actuator assembly includes a comb drive  
10 and the optical micro-element assembly includes an etched lens, a ball lens, a mirror, or the like.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A





FIG. 2B

FIG. 3







FIG. 4

FIG. 5






FIG. 6